


UHF Aerials – BLU HD SERIES **BLU5HD**





New version of one of the most successful aerial ranges on the market.

Superb electrical specifications with excellent directivity and gain.

Pre-assembled aerial: elements, mast mount and reflector clamp.

Fast and secure grid and dipole insertion onto the preassembled support.

60mm maximum mast clamp diameter and the design offers good wind loading.

Main specifications

- 5 elements
- F Connector
- Impedance adaptor
- Robust design using quality materials

- Extremely quick construction
- Pre-assembled components
- Maximum mast diameter 60mm
- Impedance 75 Ohm

		BLU5HD					
Fracarro code		217901					
Elements	No.	5					
Band		UHF					
Channels	Europe	E21 - E69					
Technical characteristics							
Bandwidth	MHz	470 – 862					
Maximum gain	dBi	15					
Front-to-back ratio	dB	30					
Return loss	dB	-16					
Beamwidth (-3dB)	•	+/-25					
Impedance	Ohm	75					
Mechanical characteristics							
Dimensions (L x W)	cm	84 x 50					
Maximum mast diameter	mm	60					
Wind load at 120Km/h (720N/m ²)	Kg (N)	5.7 (55.86)					
Connector	Туре	F					
Accessories							
Horizontal polarisation	Included						
Horizontal polarisation with tilt adj.	Included						
Vertical polarisation	Included						
Vertical polarisation with tilt adj.	Included						
Auxiliary boom	N.A.						







Fracarro code	Item	Packaging	Quantity	Dimensions	Unit weight	Total weight
			Pcs	mm	Kg	Kg
217901	BLU5HD	Box	10	890 x 395 x 490	1.75	19.4

